

FRL Mini Series

								
N010 Mini Pag. 21.4	N015 Mini Pag. 21.6	N020 Mini Pag. 21.8	N070 Mini Pag. 21.10	N080 Mini Pag. 21.12	N030 Mini Pag. 21.14	N040 Mini Pag. 21.16	N100 Mini Pag. 21.18	N400 Mini Pag. 21.20
 Accessories Pag. 21.22								

FRL Evo Series

								
N010 Pag. 21.29	N015 Pag. 21.31	N016 Pag. 21.33	N020 Pag. 21.35	N022 Pag. 21.37	N025 Pag. 21.40	N030 Pag. 21.42	N040 Pag. 21.44	N050 Pag. 21.46
								
N051 Pag. 21.50	N052 Pag. 21.52	N060 Pag. 21.54	N090 Pag. 21.56	N100 Pag. 21.58	N400 Pag. 21.60	Accessories Pag. 21.62		

Click here to view the **FRL Mini Series** on our Website



Click here to view the **FRL Evo Series** on our Website



ARI REGULATOR UNIT



FRL Series



Mini technical instruction

The FRL components must be assembled in the following order: Filter, Regulator, Lubricator.
While connecting the components, be sure that the air flows towards the direction of the arrows located on the top of the components




Assembling and Setting pressure

- 1 To set up each component, follow these steps:
 - Line up the plates up with the bodies.
 - Assemble the parts together, making sure that the o-ring seals are in their proper seats.
 - Tighten the screws on the plates.

- 2 To regulate the pressure, follow these instructions:
 - Turn the knob to the desired pressure.
 - Rotate the knob to increase or decrease the pressure.
 - Press the knob to block into position.

The pressure Gauge has to be assembled manually with the addition of liquid sealant.

The mini quick exhaust regulator allows the circuit downstream to exhaust rapidly when upstream pressure is interrupted.



Mini technical instruction

- 1 The manual/semiautomatic condensation exhaust is normally in the open position; (i.e. it automatically exhausts the condensation when there is no pressure inside the bowl). Pressing the knob will exhaust the condensation even if there is pressure. Turning the knob counter-clockwise will close off the exhaust.
- 2 To add oil to the lubricator, unscrew the plug located on the top or disassemble the bowl). Make sure that there is no pressure in the system before adding oil or disassembling the bowl.
- 3 To remove the bowl, use CH3 caliper face spanners. The transparent bowl shows the condensation level in the filter and the oil level in the lubricator.



N010 MINI

FILTER



TECHNICAL CHARACTERISTICS



Reference standard

1907/2006
REACH


2011/65/CE
RoHS

PED
2014/68/UE



Component Parts and Materials

- 1 Technopolymeric Body
- 2 Brass Threaded insert
- 3 Technopolymeric Bowl
- 4 Technopolymeric Filter ring
- 5 Technopolymeric Condensate exhaust
- 6 PE Filtering cartridge
- 7 Technopolymeric Slinger
- 8 NBR O-Ring




Part Numbering System

Code	Size	Thread	Filtration	Condensate exhaust	Flow Rate
N 0 1 0	0	0 3	2	0 1	0 0 0
		02 = 1/8 03 = 1/4	1 = 5 2 = 20 3 = 50	1 = Semi Automatic Manual	800 NI/min

	FLUID	Compressed Air
	THREAD	1/8" NPTF 1/4" NPTF
	FILTRATION GRADE	5 µm 20 µm STANDARD 50 µm
	6 bar FLOW RATE with Δp 1 bar	800 NI/min
	MAX PRESSURE	15 bar (217 psi)
	TEMPERATURE	-10 °C (14 F) + 50 °C (122 F)
	ASSEMBLY POSITION	Vertical
	BOWL CAPACITY	17.5 cm³
	CONDENSATE EXHAUST	Manual Semi Automatic

N010



Dimensions

B	C	D	E	F	H	I	J	K	L	W	Q
109	40	40	13.5	20	11	27	30	10	Ø X M3	1/8 - 1/4"	1/8

Code	Size	Thread (NPTF)	Filtration	Flow Rate (NPTF)
N010 002 201 000	FIL 0	1/8	20 µm	800 NI/min
N010 003 201 000	FIL 0	1/4"	20 µm	800 NI/min

N015 MINI

COALESCER FILTER



TECHNICAL CHARACTERISTICS



Reference standard


1907/2006
REACH ✓

2011/65/CE
RoHS ✓

PED
2014/68/UE


Component Parts and Materials

- 1 Technopolymeric Body
- 2 Brass Threaded insert
- 3 Technopolymeric Bowl
- 4 Technopolymeric Condensate exhaust
- 5 Coalescer cartridge
- 6 NBR O-Ring




	FLUID	5 µm Filtered Compressed Air
	THREAD	1/8" NPTF 1/4" NPTF
	FILTRATION GRADE	0.01 µm
	6 bar FLOW RATE with Δp 1 bar	450 NI/min
	MAX PRESSURE	15 bar (217 psi)
	TEMPERATURE	-10 °C (14 F) + 50 °C (122 F)
	ASSEMBLY POSITION	Vertical
	BOWL CAPACITY	17.5 cm³
	CONDENSATION EXHAUST	Manual Semi Automatic



Part Numbering System

Code	Size	Thread	Filtration	Condensate exhaust	Flow Rate
N 0 1 5	0	0 3 02 = 1/8 03 = 1/4	4 4 = 0,01 µm	0 1 1 = Semi Automatic Manual	0 0 450 NI/min

N015 Mini



Dimensions

B	C	D	E	F	H	I	J	K	L	W	Q
109	40	40	13.5	20	11	27	30	10	Ø X M3	1/8 - 1/4"	1/8

NB: With Coalescer filter T015 we recommend to install a 5 µm Filter upstream..

Code	Size	Thread (NPTF)	Filtration	Flow Rate (NPTF)
N015 002 401 000	FC 0	1/8	0.01 µm	450 NI/min
N015 003 401 000	FC 0	1/4"	0.01 µm	450 NI/min

N020 MINI

REGULATOR



TECHNICAL CHARACTERISTICS



Reference standard


1907/2006
REACH✓

2011/65/CE
RoHS✓

PED
2014/68/UE


Component Parts and Materials

- 1 Technopolymeric Body
- 2 Technopolymeric Bell
- 3 Technopolymeric Fixing nut
- 4 Technopolymeric Knob
- 5 Brass Register screw
- 6 Brass Female screw
- 7 Steel Register spring
- 8 Membrane Rolling
- 9 NBR Relieving diaphragm
- 10 Shutter with NBR vulcanized seal
- 11 Technopolymeric Plug
- 12 Stainless steel Push-shutter spring
- 13 NBR O-Ring
- 14 Brass Threaded insert



	FLUID	Compressed Air
	THREAD	1/8" NPTF 1/4" NPTF
	FILTRATION GRADE	0-29 psi 0-58 psi 0-116 psi (standard) 0-174 psi
	6 bar FLOW RATE with Δp 1 bar	600 NI/min
	MAX PRESSURE	15 bar (217 psi)
	TEMPERATURE	-10 °C (14 F) + 50 °C (122 F)
	ASSEMBLY POSITION	Vertical
	Gauge THREAD	G 1/8



Part Numbering System

Code

Size

Thread

Regulation

Flow Rate

N 0 2 0

0

0 3

02 = 1/8
03 = 1/4


0 0 1

1 = 0÷2 bar
2 = 0÷4 bar
3 = 0÷8 bar
4 = 0÷12 bar

0 0 0

600 NI/min

N020 Mini



Dimensions

B	C	D	E	F	G	I	M	W
74	40	40	13.5	20	27.5	27	M30X1.5	1/8 - 1/4"

Code	Size	Thread (NPTF)	Regulation	Flow Rate (NPTF)
N020 002 030 000	REG 0	1/8	0-116 psi	600 NI/min
N020 003 030 000	REG 0	1/4"	0-116 psi	600 NI/min

N070 MINI

QUICK EXHAUST REGULATOR



TECHNICAL CHARACTERISTICS



Reference standard


1907/2006
REACH ✓

2011/65/CE
RoHS ✓

PED
2014/68/UE


Component Parts and Materials

- 1 Technopolymeric Body
- 2 Technopolymeric Bell
- 3 Technopolymeric Fixing nut
- 4 Technopolymeric Knob
- 5 Brass Register screw
- 6 Brass Female screw
- 7 Steel Register spring
- 8 Membrane Rolling
- 9 NBR Relieving diaphragm
- 10 Shutter with NBR vulcanized seal
- 11 Technopolymeric Plug
- 12 Stainless steel Push-shutter spring
- 13 NBR O-Ring
- 14 Brass Threaded insert



	FLUID	Compressed Air
	THREAD	1/8" NPTF 1/4" NPTF
	FILTRATION GRADE	0-29 psi 0-58 psi 0-116 psi (standard) 0-174 psi
	6 bar FLOW RATE with Δp 1 bar	600 NI/min
	MAX PRESSURE	15 bar (217 psi)
	TEMPERATURE	-10 °C (14 F) + 50 °C (122 F)
	ASSEMBLY POSITION	Vertical
	Gauge THREAD	G 1/8



Part Numbering System

Code

Size

Thread

Regulation

Flow Rate

N 0 7 0

0

0 3

02 = 1/8
03 = 1/4


0 3 0

1 = 0÷2 bar
2 = 0÷4 bar
3 = 0÷8 bar
4 = 0÷12 bar

0 0 0

600 NI/min

N070 Mini



Dimensions

B	C	D	E	F	G	I	M	W
74	40	40	13.5	20	27.5	27	M30X1.5	1/8 - 1/4"

Code	Size	Thread (NPTF)	Regulation	Flow Rate (NPTF)
N070 002 030 000	REG. 0	1/8	0-116 psi	600 NI/min
N070 003 030 000	REG. 0	1/4"	0-116 psi	600 NI/min

N080 MINI

WATER REGULATOR



TECHNICAL CHARACTERISTICS



Reference standard

1907/2006
REACH ✓

2011/65/CE
RoHS ✓


PED
2014/68/UE


Food grade approved version also available.



Component Parts and Materials

- 1 Technopolymeric Body
- 2 Technopolymeric Bell
- 3 Technopolymeric Fixing nut
- 4 Technopolymeric Knob
- 5 Brass Register screw
- 6 Brass Female screw
- 7 Steel Register spring
- 8 Membrane Rolling
- 9 Shutter with vulcanized NBR seal
- 10 Technopolymeric Plug
- 11 Stainless steel Push-shutter spring
- 12 NBR O-Ring
- 13 Brass Threaded insert



	FLUID	Water
	THREAD	1/8" NPTF 1/4" NPTF
	FILTRATION GRADE	0-29 psi 0-58 psi 0-116 psi (standard) 0-174 psi
	MAX PRESSURE	15 bar (217 psi)
	TEMPERATURE	+ 5 °C (41 F) + 50 °C (122 F)
	ASSEMBLY POSITION	Vertical
	Gauge THREAD	G 1/8



Part Numbering System

Code

Size

Thread

Regulation

N 0 8 0

0

0 3


02 = 1/8
03 = 1/4

0 0 1

1 = 0÷2 bar
2 = 0÷4 bar
3 = 0÷8 bar
4 = 0÷12 bar

0 0 0

N080 Mini



Dimensions

B	C	D	E	F	G	I	M	W
74	40	40	13.5	20	27.5	27	M30X1.5	1/8 - 1/4"

Code	Size	Thread (NPTF)	Regulation
N080 002 030 000	WATER REG. 0	1/8	0-116 psi
N080 003 030 000	WATER REG. 0	1/4"	0-116 psi

N030 MINI

FILTER REGULATOR



TECHNICAL CHARACTERISTICS



Reference standard

1907/2006
REACH ✓


2011/65/CE
RoHS ✓

PED
2014/68/UE



Component Parts and Materials

- 1 Technopolymeric Body
- 2 Technopolymeric Bell
- 3 Technopolymeric Fixing nut
- 4 Technopolymeric Knob
- 5 Brass Register screw
- 6 Brass Female screw
- 7 Register spring made in steel
- 8 Rolling membrane
- 9 NBR Relieving diaphragm
- 10 Shutter with vulcanized NBR seal
- 11 Technopolymeric Filter ring
- 12 Technopolymeric Bowl
- 13 Technopolymeric Condensate exhaust
- 14 PE Filtering cartridge
- 15 Technopolymeric Slinger
- 16 NBR O-Ring
- 17 Brass Threaded insert




Part Numbering System

Code	Size	Thread	Filtration	Regulation	Condensate exhaust	Flow Rate
N 0 3 0	0	0 3	2	3	1	0 0 0
		02 = 1/8 03 = 1/4	1 = 5 µm 2 = 20 µm 3 = 50 µm	1 = 0÷2 bar 2 = 0÷4 bar 3 = 0÷8 bar 4 = 0÷12 bar	1 = Semi Automatic Manual	600 NI/min

	FLUID	Compressed Air
	THREAD	1/8" NPTF 1/4" NPTF
	REGULATION RANGE	0-29 psi 0-58 psi 0-116 psi (standard) 0-174 psi
	FILTRATION GRADE	5 µm 20 µm STANDARD 50 µm
	6 bar FLOW RATE with Δp 1 bar	600 NI/min
	MAX PRESSURE	15 bar (217 psi)
	TEMPERATURE	+ 5 °C (41 F) + 50 °C (122 F)
	ASSEMBLY POSITION	Vertical
	BOWL CAPACITY	17.5 cm³
	CONDENSATION EXHAUST	Manual Semi Automatic
	Gauge THREAD	G 1/8

N030 Mini



Dimensions

B	C	D	E	F	G	H	I	M	N	W
156	M30X1.5	40	13.5	20	27.5	11	27	40	40	1/8 - 1/4"

Code	Size	Thread (NPTF)	Filtration	Regulation	Flow Rate (NPTF)
N030 002 231 000	FR 0	1/8	20µm	0-116 psi	600 NI/min
N030 003 231 000	FR 0	1/4"	20µm	0-116 psi	600 NI/min

N040 MINI

LUBRICATOR



TECHNICAL CHARACTERISTICS



Reference standard


1907/2006
REACH✓

2011/65/CE
RoHS✓

PED
2014/68/UE


Component Parts and Materials

- 1 Technopolymeric Body
- 2 Technopolymeric Bowl
- 3 Brass Threaded insert
- 4 Venturi Membrane device
- 5 Oil aspiration tube made in PA11
- 6 Small filter
- 7 Trasparent technopolymeric Visual dome
- 8 Brass Oil regulating capacity pin
- 9 Brass Oil loading plug
- 10 Brass Air diffuser
- 11 NBR O-Ring




	FLUID	Compressed Air
	THREAD	1/8" NPTF 1/4" NPTF
	6 bar FLOW RATE with Δp 1 bar	700 NI/min
	MAX PRESSURE	15 bar (217 psi)
	TEMPERATURE	-10 °C (14 F) + 50 °C (122 F)
	WALL CLAMPING SCREWS	M3
	ASSEMBLY POSITION	Vertical
	BOWL CAPACITY	28 cm ³
	RECOMMENDED OILS	ISO VG 22A CLASS ISO 3448 NORMA



Part Numbering System

Code	Size	Thread	Flow Rate	Oil loading System
N 0 4 0	0	0 2	0 0 0	1 0 0
		02 = 1/8 03 = 1/4	700 NI/min	1 = Manual

N040 Mini



Dimensions

B	C	D	E	F	H	I	J	K	L	M	W
130	40	40	13.5	20	11	27	30	10	Ø X M3	33.5	1/8 - 1/4"

Code	Size	Thread (NPTF)	Flow Rate (NPTF)
N040 002 000 100	LUB 0	1/8	700 NI/min
N040 003 000 100	LUB 0	1/4"	700 NI/min

N100 MINI

FILTER REGULATOR + LUBRICATOR



TECHNICAL CHARACTERISTICS



Reference standard

1907/2006
REACH✓

2011/65/CE
RoHS✓

PED
2014/68/UE



	FLUID	Compressed Air
	THREAD	1/8" NPTF 1/4" NPTF
	FILTRATION GRADE	5 µm 20 µm STANDARD 50 µm
	REGULATION RANGE	0-29 psi 0-58 psi 0-116 psi (standard) 0-174 psi
	6 bar FLOW RATE with Δp 1 bar	260 NI/min
	MAX PRESSURE	15 bar (217 psi)
	TEMPERATURE	-10 °C (14 F) + 50 °C (122 F)
	WALL CLAMPING SCREWS	M3
	ASSEMBLY POSITION	Vertical
	BOWL CAPACITY	28 cm³
	RECOMMENDED OILS	ISO VG 22A CLASS ISO 3448 NORMA



Part Numbering System

Code	Size	Thread	Filtration	Regulation	Condensate exhaust	Oil loading System	Flow Rate
N 1 0 0	0	0 3	2	3	1	1	0 0
		02 = 1/8 03 = 1/4	1 = 5 µm 2 = 20 µm 3 = 50 µm	1 = 0÷2 bar 2 = 0÷4 bar 3 = 0÷8 bar 4 = 0÷12 bar	1 = Semi Automatic Manual	1 = Manual	260 NI/min

N100 Mini



Dimensions

B	C	D	I	J	K	L	N	W
156	40	80	27	30	10	Ø X M3	40	1/8 - 1/4"

Code	Size	Thread (NPTF)	Filtration	Regulation	Flow Rate (NPTF)
N100 002 231 100	FR+L 0	1/8	20µm	0-116 psi	260 NI/min
N100 003 231 100	FR+L 0	1/4"	20µm	0-116 psi	260 NI/min

N400 MINI

FILTER + FILTER COALESSER



TECHNICAL CHARACTERISTICS



Reference standard

1907/2006
REACH ✓

2011/65/CE
RoHS ✓

PED
2014/68/UE

	FLUID	Compressed Air
	THREAD	1/8" NPTF 1/4" NPTF
	FILTRATION GRADE	5 µm + 0.01 µm
	6 bar FLOW RATE with Δp 1 bar	370 NI/min
	MAX PRESSURE	15 bar (217 psi)
	TEMPERATURE	-10 °C (14 F) + 50 °C (122 F)
	WALL CLAMPING SCREWS	M3
	ASSEMBLY POSITION	Vertical



Part Numbering System

Code	Size	Thread	Filtration	Condensate exhaust	Flow Rate
N 4 0 0	0	0 3	4	0 1	0 0 0
		02 = 1/8 03 = 1/4	4 = 0.01 µm	1 = Semi Automatic Manual	370 NI/min




Information

The coalescer cartridge is made of a microfiber inner layer with an external stainless steel structure.


The coalescing cartridge uses inertial impact, interception and coalescence to collect excess liquid. This liquid will then drain into the bottom of the bowl.

The coalescing filter is used as oil separator which removes oil-vapours from the air output.

We recommend installing a 5 µm filter upstream to protect the coalescing filter from choking the cartridge.



N400 Mini



Dimensions

B	C	D	I	J	K	L	W
109	40	80	27	30	10	Ø X M3	1/8 - 1/4"

Code	Size	Thread (NPTF)	Filtration	Flow Rate (NPTF)
N400 002 401 000	FIL+FC 0	1/8	5µm + 0.01µm	370 NI/min
N400 003 401 000	FIL+FC 0	1/4"	5µm + 0.01µm	370 NI/min

FRL ACCESSORIES

T500

CONNECTION PLATE



Code

T500 000 000 000

FRL 0

T520

BOWL FOR FILTER UNIT



Code

T520 000 001 000

FRL 0

T530

BOWL FOR LUBRICATOR UNIT



Code

T530 000 000 100

FRL 0

T545

COALESCER FILTER





Code

T545 000 000 000

FRL 0

DIS00

AIR DISTRIBUTOR



Code		A	B	C	D
DIS00 001 100 NE	FRL 0	27	40	1/8	30

FIL04

SINTERED FILTER



Code		
FIL04 003 805 SC	FRL 0	5 µm
FIL04 003 820 SC	FRL 0	20 µm
FIL04 003 850 SC	FRL 0	50 µm

REG06

REGISTER SPRING



Code		
REG06 005 401 SC	FRL 0	0-29 psi
REG06 005 402 SC	FRL 0	0-58 psi
REG06 005 403 SC	FRL 0	0-116 psi (standard)
REG06 005 404 SC	FRL 0	0-174 psi

REG09

MEMBRANE



Code	
REG09 001 700 SC	FRL 0

REG16

CLAMP BRACKET

Code		A	B	C	D	F
REG16 005 000 NE	FRL 0	21.5	5.5	12	15	31

