

Actuators Series

Cartidge Cylinders
Ø 6-16 mm



CA - CAF Series

Pg. 20.3

Mini Cylinders ISO 6432
Ø 8-25 mm



Mini Series

Pg. 20.5

Mini Stainless Steel Cylinders
ISO 6432 Ø 16-25 mm



Mini Stainless Steel Series

Pg. 20.13

Limited Space
Ø 32-63 mm



A95 Series

Pg. 20.16

Compact Cylinders
Ø 12-100 mm



Q Series

Pg. 20.23

ISO 15552 Cylinders
Ø 32-125 mm



L Series

Pg. 20.36

ISO 6431 Cylinders
Ø 160-320 mm



E Series

Pg. 20.45

Stainless Steel ISO 15552 Cylinders
Ø 32-125 mm



V Series

Pg. 20.47

Twin Rod Cylinders
Ø 32-100 mm



NHA Series

Pg. 20.50

Compact Cylinders ISO 21287
Ø 20-100 mm



W Series

Pg. 20.54

Cylinder Accessories
ISO 6431 - ISO 15552 - ISO 21287



Accessories

Pg. 20.62

Magnetic Poition Sensing Switches



Sensor

Pg. 20.72

Rodless Actuators Series

Rodless Cylinders Standard Version



S1 Series

Pg. 20.78

Rodless Cylinder with Integrated
Guides in Tecnopolymer



S5 Series

Pg. 20.87

Click here to view the **Actuators Series** on our Website



PNEUMATIC ACTUATORS




Actuators Series

SERIES A95 - LIMITED SPACE CYLINDERS



TECHNICAL CHARACTERISTICS



Component Parts and Materials

- 1 Zinc plated steel rod jam nut
- 2 Chrome plated steel piston rod
- 3 Polyurethane rod seal
- 4 Anodized aluminum end cap
- 5 Zinc plated mounting nut
- 6 Sintered bronze rod bearing
- 7 NBR o-ring seals
- 8 Neoprene bumper
- 9 Anodized aluminum piston
- 10 Polyurethane piston seal
- 11 Bonded ferrite magnet
- 12 304 Stainless steel body
- 13 Anodized aluminum end cap



Reference Standard

1907/2006
REACH ✓

2011/65/CE
RoHS ✓

PED
2014/68/UE

SILICON
FREE

ATEX
2014/34/UE



Pressures

- 1 bar (0.1 MPa) / 14.5 psi
10 bar (1 MPa) / 145 psi



Temperatures

- 0 °C / 32 °F (-20 °C / -4 °F with dry air)
+ 80 °C / 176 °F



Media

Filtered and lubricated or non-lubricated compressed air.



Functions

Single acting magnetic or non-magnetic. Double acting single or double rod end, magnetic or non-magnetic, cushioned or non-cushioned.



Bores

32 - 40 - 50 - 63 mm



Standard Strokes

from 10 to 500 mm



FORCES, SPRING LOADS AND AIR CONSUMPTION

Extend and Retract Forces

Cylinder Ø	Piston Rod Ø	Piston Area mm ²	Operating pressure									
			bar									
			1	2	3	4	5	6	7	8	9	10
Output force N												
32	12	Extend = 804	72	144	216	288	360	432	504	576	648	720
		Retract = 691	62	124	186	248	310	372	434	496	558	620
40	16	Extend = 1257	110	220	330	440	550	660	770	880	990	1100
		Retract = 1056	95	190	285	380	475	570	665	760	855	950
50	20	Extend = 1963	175	350	525	700	875	1050	1225	1400	1575	1750
		Retract = 1649	148	296	444	592	740	888	1036	1184	1332	1480
63	20	Extend = 3117	280	560	840	1120	1400	1680	1960	2240	2520	2800
		Retract = 2803	250	500	750	1000	1250	1500	1750	2000	2250	2500

Spring Loads

Cylinder		Spring load	Stroke (mm)	
Ø		10	25	50
Output force N				
32	Load of spring at rest	56	51	42
	Load of compressed spring	60	60	60
40	Load of spring at rest	60	55	44
	Load of compressed spring	65	65	65
50	Load of spring at rest	64	57	46
	Load of compressed spring	68	68	68
63	Load of spring at rest	65	58	47
	Load of compressed spring	70	70	70

Air Consumption



Cylinder Ø	Piston Rod Ø	Piston Area mm ²	Operating pressure									
			bar									
			1	2	3	4	5	6	7	8	9	10
Air consumption for each 10 mm of stroke NI												
32	12	Extend = 804	0.016	0.024	0.032	0.040	0.048	0.056	0.064	0.072	0.080	0.088
		Retract = 691	0.014	0.021	0.028	0.035	0.041	0.048	0.055	0.062	0.069	0.076
40	16	Extend = 1257	0.025	0.038	0.050	0.063	0.075	0.088	0.101	0.113	0.126	0.138
		Retract = 1056	0.021	0.032	0.042	0.053	0.063	0.074	0.084	0.095	0.106	0.116
50	20	Extend = 1963	0.039	0.059	0.079	0.098	0.118	0.137	0.157	0.177	0.196	0.216
		Retract = 1649	0.033	0.049	0.066	0.082	0.099	0.115	0.132	0.148	0.165	0.181
63	20	Extend = 3117	0.062	0.094	0.125	0.156	0.187	0.218	0.249	0.281	0.312	0.343
		Retract = 2803	0.056	0.084	0.112	0.140	0.168	0.196	0.224	0.252	0.280	0.308

Series	Ø (mm)	Stroke (mm)
A B	0 3 2	0 0 2 5
▲ AB Single acting - magnetic	032	0010 0160
▲ AD Single acting - magnetic - spring extend	040	0025 0200
● AF Double acting - magnetic	050	0050 0250
◆ AH Double acting - cushioned - magnetic	063	0080 0320
● AJ Double acting - magnetic with double rod end		0100 0400
◆ AL Double acting - cushioned - magnetic with double rod end		0125 0500
		0150
		Intermediate or longer strokes are available upon request.

Ø (mm)	Stroke (mm)											
	10	25	50	80	100	125	160	200	250	320	400	500
32	▲ ●	▲ ◆ ●	▲ ◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●
40	▲ ●	▲ ◆ ●	▲ ◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●
50	▲ ●	▲ ◆ ●	▲ ◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●
63	▲ ●	▲ ◆ ●	▲ ◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●	◆ ●

AB


SINGLE ACTING - MAGNETIC



Ø	A	A1	B	T	C	D	F	G	K	L	P	P ₁	CH	R
32	M10x1.25	12	M30x1.5	36.5	38	14	30	168	38	20	96	125	10	1/8" GAS
40	M12x1.25	16	M38x1.5	44	46	16	35	196	45	24	111	144	12	1/4" GAS
50	M16x1.5	20	M45x1.5	55	57	18	38	220	50	32	120	158	16	1/4" GAS
63	M16x1.5	20	M45x1.5	67.5	70	18	38	224	50	32	124	161	16	3/8" GAS

AD



SINGLE ACTING - MAGNETIC - SPRING EXTEND



Ø	A	A1	B	T	C	D	F	G	K	L	P	P ₁	CH	R
32	M10x1.25	12	M30x1.5	36.5	38	14	30	168	38	20	96	125	10	1/8" GAS
40	M12x1.25	16	M38x1.5	44	46	16	35	196	45	24	111	144	12	1/4" GAS
50	M16x1.5	20	M45x1.5	55	57	18	38	220	50	32	120	158	16	1/4" GAS
63	M16x1.5	20	M45x1.5	67.5	70	18	38	224	50	32	124	161	16	3/8" GAS

AF



DOUBLE ACTING - MAGNETIC



Ø	A	A1	B	T	C	D	F	G	K	L	P	P ₁	CH	R
32	M10x1.25	12	M30x1.5	36.5	38	14	30	134	38	20	96	168	10	1/8" GAS
40	M12x1.25	16	M38x1.5	44	46	16	35	156	45	24	111	196	12	1/4" GAS
50	M16x1.5	20	M45x1.5	55	57	18	38	170	50	32	120	220	16	1/4" GAS
63	M16x1.5	20	M45x1.5	67.5	70	18	38	174	50	32	124	224	16	3/8" GAS

AH



DOUBLE ACTING - CUSHIONED - MAGNETIC



Ø	A	A1	B	T	C	D	F	G	K	L	P	P ¹	CH	R
32	M10x1.25	12	M30x1.5	36.5	38	14	30	134	38	20	96	168	10	1/8"GAS
40	M12x1.25	16	M38x1.5	44	46	16	35	156	45	24	111	196	12	1/4"GAS
50	M16x1.5	20	M45x1.5	55	57	18	38	170	50	32	120	220	16	1/4"GAS
63	M16x1.5	20	M45x1.5	67.5	70	18	38	174	50	32	124	224	16	3/8"GAS

AJ



DOUBLE ACTING - MAGNETIC WITH DOUBLE ROD END



Ø	A	A1	B	T	C	F	K	L	P	CH	R
32	M10x1.25	12	M30x1.5	36.5	38	30	38	20	96	10	1/8"GAS
40	M12x1.25	16	M38x1.5	44	46	35	45	24	111	12	1/4"GAS
50	M16x1.5	20	M45x1.5	55	57	38	50	32	120	16	1/4"GAS
63	M16x1.5	20	M45x1.5	67.5	70	38	50	32	124	16	3/8"GAS

AL


DOUBLE ACTING - CUSHIONED - MAGNETIC WITH DOUBLE ROD END



Ø	A	A1	B	T	C	F	K	L	P	CH	R
32	M10x1.25	12	M30x1.5	36.5	38	30	38	20	96	10	1/8"GAS
40	M12x1.25	16	M38x1.5	44	46	35	45	24	111	12	1/4"GAS
50	M16x1.5	20	M45x1.5	55	57	38	50	32	120	16	1/4"GAS
63	M16x1.5	20	M45x1.5	67.5	70	38	50	32	124	16	3/8"GAS

A95 Cylinder Mounting Accessories


ACC

CLEVIS BRACKET WITH PINS


MATERIAL: Steel

Code	Ø	D1	D2	A	A1	G	M1	N1	N2	R1	S	CH2	B1	B2	B3	V	C1	C2
ACC 032	32	10	16	7	35	20	M8x1	24	40	12	4	13	20	50.1	38.1	4	6	18
ACC 040	40	12	18	9	40	27	M10x1	30	50	13	5	17	28	60.1	46.1	5	7	21.6
ACC 050	50	14	23	9	45	30	M12x1.5	34	54	14	6	19	34	74.1	57.1	6	9	26.4
ACC 063	63	16	24	9	50	34	M14x1.5	35	65	16	6	19	42	88.1	70.1	6	15	34


APD

FOOT FLANGE


MATERIAL: Steel

Code	Ø	E	E2	E3	C1	C2	L2	L3	B3	B4	S	A1	A2	A3
APD 032	32	7	28	49	14	28	124	148	52	66	4	48	14	7
APD 040	40	9	33	58	18	30	151	176	60	80	5	60	20	10
APD 050	50	9	40	70	20	40	160	190	70	90	6	64	20	10
APD 063	63	9	45	80	20	50	164	194	76	96	6	65	20	10


AGT

MOUNTING NUT


MATERIAL: Steel

Code	B	D	H
AGT 032	M30x1.5	45	7
AGT 040	M38x1.5	50	8
AGT 050	M45x1.5	58	9

APE

HEAD TRUNNION


MATERIAL: Steel


Code	Ø	D	H	L1	L2	L	CH
APE 032	32	10	51	125	78	47	5
APE 040	40	12	61	144	87	57	6
APE 050	50	14	75	158	96	62	6
APE 063	63	16	90	161	98	63	8

DA

ROD JAM NUT

MATERIAL: Steel


Code	A	B	C
ODA00 00 51 C9 ZI	M10x1.25	17	8
ODA00 00 51 D5 ZI	M12x1.25	19	7
ODA00 00 51 E3 ZI	M16x1.5	22	6



FC

ROD CLEVIS WITH LOCKABLE PIN


MATERIAL: Steel



Code	KK	A	B	C	E	F	G
FC 025	M10x1.25	52	20	40	20	10	10
FC 040	M12x1.25	62	24	48	24	12	12
FC 050	M16x1.5	83	32	64	32	16	16

TF

SELF-LUBRICATING SPHERICAL ROD EYE



MATERIAL: Steel

Code	F	A	B	C	Ø Sphere	D	E	G	H	L	M	P	S	W	Radial load		Weight
															Dynamic	Static	
		H7	0	0 -0.13		± 0.13	± 0.5	± 0.5		± 0.7	± 0.7	± 0.5	+0.2 -0.7	± 0.25	kg	kg	g
TF 025	M10x1.25	10	12.9	14	19.05	11.5	30	43	58	15	15	19	6.5	16	1.200	3.100	88
TF 040	M12x1.25	12	15.4	16	22.23	12.5	34	50	67	18	17.5	22	6.5	18	1.400	3.700	120
TF 050	M16x1.5	16	19.3	21	28.58	15.5	42	64	85	24	22	27	8	24	2.500	6.300	240